


PNEED PNEUMATICS NOW?




Viking Lite

Ports

- P2LBZ: 1/4 inch NPT & BSPP, Cv = 1.5
- P2LCZ: 3/8 inch NPT & BSPP, Cv = 2.5

Single and Double Solenoid Operated Valves

P2L B Z 5 92 E S N D B B 49



* Not available with 3-position valves.

P2LBZ392ESNDBB49	3/2 Single Solenoid 1/4" NPT 24VDC In-line Valve
P2LBZ392ESNDBB53	3/2 Single Solenoid 1/4" NPT 120VAC In-line Valve
P2LCZ393ESNDBB49	3/2 Single Solenoid 3/8" NPT 24VDC In-line Valve
P2LCZ393ESNDBB53	3/2 Single Solenoid 3/8" NPT 120VAC In-line Valve
P2LBZ592ESNDBB49	5/2 Single Solenoid 1/4" NPT 24VDC In-line Valve
P2LBZ592ESNDBB53	5/2 Single Solenoid 1/4" NPT 120VAC In-line Valve
P2LCZ593ESNDBB49	5/2 Single Solenoid 3/8" NPT 24VDC In-line Valve
P2LCZ593ESNDBB53	5/2 Single Solenoid 3/8" NPT 120VAC In-line Valve
P2LBZ592EENDBB49	5/2 Double Solenoid 1/4" NPT 24VDC In-line Valve
P2LBZ592EENDBB53	5/2 Double Solenoid 1/4" NPT 120VAC In-line Valve
P2LCZ593EENDBB49	5/2 Double Solenoid 3/8" NPT 24VDC In-line Valve
P2LCZ593EENDBB53	5/2 Double Solenoid 3/8" NPT 120VAC In-line Valve
P2LBZ692EENDBB49	5/3 APB Double Solenoid 1/4" NPT 24VDC In-line Valve
P2LBZ692EENDBB53	5/3 APB Double Solenoid 1/4" NPT 120VAC In-line Valve
P2LCZ693EENDBB49	5/3 APB Double Solenoid 3/8" NPT 24VDC In-line Valve
P2LCZ693EENDBB53	5/3 APB Double Solenoid 3/8" NPT 120VAC In-line Valve
PS2430J79BP	22mm 3 Pin Connector 6' Cord Light 24VDC
PS243079BP	22mm 3 Pin Connector Light 24VDC
PS2430J83BP	22mm 3 Pin Connector 6' Cord Light 120VAC
PS243083BP	22mm 3 Pin Connector Light 120VAC



RAPID RESERVE

ALWAYS AVAILABLE STOCK

Look for these products ready to ship!

Don't sweat it, getting your hands on the world-class pneumatic components you need has never been easier. These **RG Rapid Reserve** products are always available and shipped same day.



RG Group

www.rg-group.com

MODUFLEX

Ports


- Size 1: Push-in connectors for 1/4 inch Cv = 0.18 - 0.32
- Size 2: Push-in connectors for 1/4, 3/8 Cv = 0.44 - 0.80

Mounting

- T Series - Manifold mount with individual connectors
- V Series - Manifold mount with collective wiring or fieldbus

CMD07-1B	Size 1 PTC 1/4" Elbow
FMD07-1B	Size 1 PTC 1/4" Straight
P2M1K0TASD	TORX screwdriver
P2M2HXT01	End Plate Kit
CMD07-2B	Size 2 PTC 1/4" Elbow
FMD07-2B	Size 2 PTC 1/4" Straight
CMD09-2B	Size 2 PTC 3/8" Elbow
FMD09-2B	Size 2 PTC 3/8" Straight
FMD13-2B	Size 2 PTC 1/2" Straight
MMDVA2	Size 2 Exhaust Muffler

"T" Series Valve Manifold with individual connectors (Complete with pneumatic and electrical connectors)




P2M1T4ES2C	T Series Size 1 4/2 Single Solenoid 24VDC
P2M1T4EE2C	T Series Size 1 4/2 Double Solenoid 24VDC
P2M1TJEE2C	T Series Size 1 Dual 4/2 Double Solenoid 24VDC
P2M1T3ES2C	T Series Size 1 3/2 NC Single Solenoid 24VDC
P2M1TGEE2C	T Series Size 1 Dual 3/2 NC Double Solenoid 24VDC
P2M2T4ES2C	T Series Size 2 4/2 Single Solenoid 24VDC
P2M2T4EE2C	T Series Size 2 4/2 Double Solenoid 24VDC
P2M2T3ES2C	T Series Size 2 3/2 NC Single Solenoid 24VDC
P2M2TGEE2C	T Series Size 2 Dual 3/2 NC Double Solenoid 24VDC
P8LS08L226C	.M8 IP67 2 Meter Cable



Place order by 3:00pm for next day* shipment. *Quantities may be limited



"V" Series Valve Manifold with collective wiring (Complete with pneumatic connectors)



P2M1V4ES2CV	V Series Size 1 4/2 Single Solenoid 24VDC
P2M1V4EE2CV	V Series Size 1 4/2 Double Solenoid 24VDC
P2M1VJEE2CV	V Series Size 1 Dual 4/2 Double Solenoid 24VDC
P2M1VDDEE2CV	V Series Size 1 Dual 3/2 NC Double Solenoid 24VDC
P2M1V3ES2CV	V Series Size 1 3/2 NC Single Solenoid 24VDC
P2M2V4ES2CV	V Series Size 2 4/2 Single Solenoid 24VDC
P2M2V4EE2CV	V Series Size 2 4/2 Double Solenoid 24VDC
P2M2VDDEE2CV	V Series Size 2 Dual 3/2 NC Double Solenoid 24VDC
P2M2V3ES2CV	V Series Size 2 3/2 NC Single Solenoid 24VDC
P8LMH25M3A	.25 Pin D Sub IP20 3 Meter Cable
P2M2HEV0D	.25 Pin D Sub Head Module



Engineered Systems and Solutions

RG Group Engineered Solutions team provides innovative systems that range from single custom machine control packages to long-term flexible outsourced manufacturing services. Our Tri-Technology **hydraulic, pneumatic and electromechanical** capabilities allow us to specify the appropriate mechanical products for your application.

We've developed the technical expertise to take your projects from start to finish, from concept and feasibility studies through design, manufacturing, installation and even the commissioning process. Our solutions aren't off the shelf, we create just what YOU need because **true innovation doesn't come with a part number.**

P: 877.870.2692 F: 877.727.4332

customer.service@rg-group.com

www.rg-group.com

RG Group

Innovative Motion Control and Fluid Handling Products and Solutions

Allegheny Fluid Power | Powertech | Marine Systems | Weaver Fluid Power

ISYS MICRO

Cv up to 0.35

Ports

- M7 on manifolds
- 3/8 Inch on end plates

Mounting

- Manifold

Solenoids

- 24 VDC, 1.0 watt



HMEVX2049A	5/2 Single Solenoid 24VDC
HM2VX2049A5/2 Double Solenoid 24VDC
HM5VX2049A5/3 APB Double Solenoid 24VDC
HMBVX00XXA	Blanking Plate
PSM21MAP	Side Ported Double Address Base
PSML25AP	25 Pin D Sub Side NPT Port End Plate Kit
P6M-PAB3	3/8" NPT Main Exhaust Muffler
PS567925	1/4" PTC Manifold Fitting
PS568325	1/4" PTC Main Inlet Fitting
PS568338	3/8" PTC Main Inlet Fitting

Certification / approval

- IP65 rated
- EMC / CE Mark: According to EN 61 000-6-2



Ports, Flow

- HA: 1/4 inch, 1.1 Cv
- H1: 3/8 inch, 1.5 Cv

15407-2, Plug-in, Size 18mm (HB) and 26mm (HA)

HA 2 VX B G 0 23 A

Basic series 15407-2 ISO 15407-2 26mm HA	15407-2 Engineering level A Current
15407-2 Operator / Function Double solenoid, 2-position 2 Double solenoid, 3-position - APB 5 Single solenoid, 2-position - air return, spring assist E	15407-2 Voltage and frequency AC DC Light and surge suppression 60Hz 50Hz 69 24 LED and suppression 23 120 115 LED and suppression
Mounting 15407-2 Valve less base VX	15407-2 Enclosure / Lead length 0 Valve less base
15407-2 Pilot source / Pilot exhaust Internal pilot, port#1 / vented B	15407-2 Pilot Overrides / Lights G Non-locking, flush, push - w/light

5599-2, Plug-in, Size 1

H1 E VX B G 0 B9 D

Basic series 5599-2 ISO 5599-2 Size 1 H1	5599-2 Engineering level D Current
5599-2 Operator / Function Double solenoid, 2-position 2 Double solenoid, 3-position - APB 5 Single solenoid, 2-position - air return, spring assist E	5599-2 Voltage and frequency AC DC Light and surge suppression 60Hz 50Hz B9 24 LED and suppression 23 120 115 LED and suppression
5599-2 Mounting 5599-2 Valve less base VX	5599-2 Enclosure / Lead length 0 None, valve less base
5599-2 Pilot source / Pilot exhaust Internal pilot, port#1 / vented B	5599-2 Pilot Overrides / Lights Voltage code G B9, 23 Non-locking, flush, push - w/light

ISYS ISO HA

HAEVXBG0G9A	4/2 Single Solenoid 24VDC
HA2VXBG0G9A	4/2 Double Solenoid 24VDC
HA5VXBG0G9A	4/3 APB Double Solenoid 24VDC
HAEVXBG023A	4/2 Single Solenoid 120VAC
HA2VXBG023A	4/2 Double Solenoid 120VAC
HA5VXBG023A	4/3 APB Double Solenoid 120VAC
PS551153MP	1/4" NPT End Ported Double Address Manifold Base
PS5620L20P25 Pin D-Sub End Plate Kit

ISYS ISO H1

H1EVXBG0B9D	4/2 Single Solenoid 24VDC
H12VXBG0B9D	4/2 Double Solenoid 24VDC
H15VXBG0B9D	4/3 APB Double Solenoid 24VDC
H1EVXBG023D	4/2 Single Solenoid 120VAC
H12VXBG023D	4/2 Double Solenoid 120VAC
H15VXBG023D	4/3 APB Double Solenoid 120VAC
PS401165MCP	3/8" NPT Double Address Manifold Base
PS4020L20CP25 Pin D-Sub End Plate Kit

Electronic Automation

RG Group is committed to bringing you the most comprehensive array of automation and electronic products and technologies, but we're much more than just great parts from quality manufacturers. Our engineers will help specify and evaluate the products you need for assembly applications. Whether your needs are simple or sophisticated, we offer the flexibility and options to meet and exceed them.

- HMI (human-machine interface)
- motion controllers
- drives
- RFID systems
- linear transducers
- proximity and level sensors
- photoelectric sensors
- vision systems
- pressure switches and transducers

GLOBAL FRL

P31FB92EGMN	1/4" 5 Micron Poly Bowl w/Guard Manual Drain Filter
P31KA00ESE	5 Micron Replacement Element
P31KA00MW	C Bracket
P31KA00MT	T Bracket With Body Connector
P31KA00CB	Body Connector
P32FB93EGMN	3/8" 5 Micron Poly Bowl w/Guard Manual Drain Filter
P32KA00ESE	5 Micron Replacement Element
P32KA00ML	L Bracket
P32KA00MT	T Bracket With Body Connector
P32KA00CB	Body Connector
P33FA94EGMN	1/2" 5 Micron Poly Bowl w/Guard Manual Drain Filter
P33KA00ESE	5 Micron Replacement Element
P33KA00ML	L Bracket
P31RB92BN5P	1/4" Relieving 125 PSI w/Square Gauge Regulator
P31HB92BNNP	1/4" Relieving 125 PSI Common Port Regulator
P32RB93BN5P	3/8" Relieving 125 PSI w/Square Gauge Regulator
P32KB00MR	Angle Bracket
P32HB93BNNP	3/8" Relieving 125 PSI Common Port Regulator
P33RA94BNGP	1/2" Relieving 125 PSI w/Round Gauge Regulator
P33KA00MR	Angle Bracket
P31EB92EGMBN5P	1/4" 5 Micron Poly Bowl w/Guard Manual Drain 125 PSI w/Square Gauge Filter/Regulator
P32EB93EGMBN5P	3/8" 5 Micron Poly Bowl w/Guard Manual Drain 125 PSI w/Square Gauge Filter/Regulator
P33EA94EGMBNGP	1/2" 5 Micron Poly Bowl w/Guard Manual Drain 125 PSI w/ Round Gauge Filter/Regulator
P31VB92LBNN	1/4" Ball/Lock Out Valve
P32VB93LBNN	3/8" Ball/Lock Out Valve
P33VB94LBNN	1/2" Ball/Lock Out Valve



Air Preparation

P31 Mini Series

40mm body width, 1/4" Ported

Flows up to:	dm3/s	(SCFM)
Filter	12	(25)
Regulator	32	(68)
Filter/Regulator	10	(22)

Features:

- Space saving integral gauge
- Manifold style regulators available
- OSHA compliant shut-off valves
- Soft-Start and Quick Dump valves
- Electronic Proportional Regulator

P32 Compact Series

60mm body width, 3/8" Ported

Flows up to:	dm3/s	(SCFM)
Filter	39	(82)
Regulator	78	(165)
Filter/Regulator	64	(136)

Features:

- Manifold style regulators available
- OSHA Compliant shut-off valves
- Soft-Start and Quick Dump valves
- Electronic Proportional Regulator

P33 Standard Series

73mm body width, 1/2" Ported

Flows up to:	dm3/s	(SCFM)
Filter	48	(102)
Regulator	100	(212)
Filter/Regulator	98	(208)

Features:

- OSHA Compliant shut-off valves
- Soft-Start and Quick Dump valves (Utilizes P32 size only)
- Electronic proportional regulator (Utilizes P32 size only)



You won't even have to practice your begging skills

Relax, the speedy turnaround doesn't change our dedication to quality and superior service one bit. Talk to your sales representative today for more details, or call us at **1.877.870.2692** to get your products on the fast track!

Place order by 3:00pm for next day* shipment on these pneumatic components.

*Quantities may be limited

