BAYONET SERIES CONNECTOR

The BCF Series, designed for blood pressure monitoring devices, is a small bore, bayonet-style female connector with leak-free performance. Featuring a quick disconnect thumb latch, the single-hand operation of the BCF Series makes it the choice for fast and easy connections between blood pressure cuff and machine. Made primarily from ABS thermoplastic, the BCF Series provides an easier to use alternative to metal connector options. The BCF Series is compatible with ISO 80369-5 compliant FitQuik[™] Bayonet Fittings and standard blood pressure male fittings available in the market.

FEATURES

Small bore bayonet style connector

Secure, reliable connection Thumb latch with audible CPC click

Compatibility

BENEFITS

Eliminates potential misconnections with luer fittings

Provides proven leak-free performance

Assures one hand operation with a reliable connection $% \left({{{\bf{n}}_{{\rm{s}}}}} \right)$

Mates with CPC FitQuik blood pressure fittings as well as bayonet style fittings in the market

Visit us at cpcworldwide.com or call 800-444-2747 to get a free catalog or to find your local distributor.

Specifications

PRESSURE:

Vacuum up to 20 psi, 1.38 bar

TEMPERATURE: 32°F to 122°F (0°C to 50°C)

MATERIALS:

Main Components: ABS Thumb latch: Acetal Springs: 316 Stainless steel O-rings: Buna-N

COLOR: Gray with white latch

TUBING SIZES: 1/8" to 5/32" ID, 3.2 mm to 4.0 mm

COMPLIANCE: REACH Rohs

WARNING: Pressure, temperature, chemicals, and operating environment can affect the performance of couplings. It is the customer's responsibility to test the suitability of CPC's products in their own application conditions.

These graphics are applicable to single line use and intended to give a general idea of the performance capabilities. The shaded area of each graph represents the operating range of the product family i.e. upper and lower values are shown. Therefore, depending on the exact coupling configurations selected, you can reasonably expect values to fall within the shaded area.





BAYONET SERIES DIMENSIONS



Female Bayonet Body • ABS

TERMINA IN-LINE H	TION HOSE BARB 5/32" ID	METRIC EQ. 3.2 mm ID 4.0 mm ID	<i>Straight thru</i> BCF497 BCF597	A 0.62 0.62	B 1.24 1.24	C 1.00 1.00	D 0.45 0.45	

Male Bayonet Insert • NYLON

*	PART NO. BC330 BC331	DESCRIPTION White Nylon Male Bayonet Fitting to 3/32" Hose Barb Black Nylon Male Bayonet Fitting to 3/32" Hose Barb
A COL	PART NO. BC430 BC431	DESCRIPTION White Nylon Male Bayonet Fitting to 1/8" Hose Barb Black Nylon Male Bayonet Fitting to 1/8" Hose Barb
X	PART NO. BC530 BC531	DESCRIPTION White Nylon Male Bayonet Fitting to 5/32" Hose Barb Black Nylon Male Bayonet Fitting to 5/32" Hose Barb
- Sta	PART NO. BCG30 BCG31	DESCRIPTION White Nylon Male Bayonet Fitting to 3/16" Hose Barb Black Nylon Male Bayonet Fitting to 3/16" Hose Barb



COLDER PRODUCTS COMPANY U.S.A.

PHONE +1 651-645-0091 FAX +1 651-645-5404 TOLL FREE 800-444-2474 COLDER PRODUCTS COMPANY GMBH Germany

PHONE +49-6026-9973-0 FAX +49-6026-9973-173 COLDER PRODUCTS COMPANY LIMITED Hong Kong

PHONE +852-2987-5272 FAX +852-2987-2509

Smart fluid handling to take you forward, faster.

cpcworldwide.com/ContactUs

WARRANTY: All sales are subject to Colder Products Company's limited express warranty set forth in the CPC catalog. Contact your local distributor or CPC Customer Service for warranty provisions.

Warning: Due to the wide variety of possible fluid media and operating conditions, unintended consequences may result from the use of this product, all of which are beyond the control of Colder. It is the user's responsibility to carefully determine and test for compatibility for use with their application. All such risks shall be assumed by the buyer.

COPYRIGHT © 2016 BY COLDER PRODUCTS COMPANY, COLDER PRODUCTS COMPANY, COLDER PRODUCTS AND CPC ARE REGISTERED TRADEMARKS WITH THE US PATENT & TRADEMARK OFFICE.